



WarmMat



The WarmMat floor warming system includes a heating cable woven into an adhesive-backed fiberglass mesh that allows for simple roll-out installation without worrying about heating cable spacing.

WarmMat Floor warming mat System

Combined the highest comfort levels with maximum energy efficiency. It's a proven technology that's safe, reliable and energy efficient.

- Single point connection
- Twin-conductor cable
- Emits zero EMF (electromagnetic fields)
- Safety approved for wet locations
- Flexible installation
- Durable construction
- 25 years limited warranty

WarmMat Specifications

Cable Construction:	Twin conductor
Rated Voltage:	120V,240V
Output:	12W/ft ² (130W/m ²)±10%
Cable spacing:	3" (76.2mm)
Cable Diameter:	1/8"-1/6" (3.2mm-4.2mm)
Conductor Insulation:	Fluoropolymer
Outer Insulation:	Fluoropolymer or PVC
Max. Ambient Temp.:	85 °F (30 °C)
Min. Installation Temp.:	40 °F (5 °C)
Cold lead	10ft (3m) length

1 Warmmat heating mat 2 Instruction manual 3 Warranty card 4 16mm plastic tube

Ordering Information

120V Catalog Number	Heated Area		Mat Dimensions		Watts (12W/sq.ft.)	Amps	ohms
	sq.ft.	m ²	in.*ft.	m*m			
WarmMat-010-1	10	0.93	20*6.1	0.5*1.9	120	1.0	120.0
WarmMat-015-1	15	1.39	20*9.1	0.5*2.8	180	1.5	80.0
WarmMat-020-1	20	1.86	20*12.2	0.5*3.7	240	2.0	60.0
WarmMat-025-1	25	2.32	20*15.2	0.5*4.6	300	2.5	48.0
WarmMat-030-1	30	2.79	20*18.3	0.5*5.6	360	3.0	40.0
WarmMat-035-1	35	3.25	20*21.3	0.5*6.5	420	3.5	34.3
WarmMat-040-1	40	3.72	20*24.4	0.5*7.4	480	4.0	30.0
WarmMat-050-1	50	4.65	20*30.5	0.5*9.3	600	5.0	24.0
WarmMat-060-1	60	5.57	20*36.6	0.5*11.1	720	6.0	20.0
WarmMat-070-1	70	6.50	20*42.7	0.5*13.0	840	7.0	17.1
WarmMat-080-1	80	7.43	20*48.8	0.5*14.9	960	8.0	15.0
WarmMat-090-1	90	8.36	20*54.9	0.5*16.7	1080	9.0	13.3
WarmMat-100-1	100	9.29	20*61.0	0.5*18.6	1200	10.0	12.0



WarmMat

Ordering Information

240V Catalog Number	Heated Area		Mat Dimensions		Watts (12W/sq.ft.)	Amps	ohms
	sq.ft.	m ²	in.*ft.	m*m			
WarmMat-020-2	20	1.86	20*12.2	0.5*3.7	240	1.0	240.0
WarmMat-030-2	30	2.79	20*18.3	0.5*5.6	360	1.5	160.0
WarmMat-035-2	35	3.25	20*21.3	0.5*6.5	420	1.8	137.1
WarmMat-040-2	40	3.72	20*24.4	0.5*7.4	480	2.0	120.0
WarmMat-050-2	50	4.65	20*30.5	0.5*9.3	600	2.5	96.0
WarmMat-060-2	60	5.57	20*36.6	0.5*11.1	720	3.0	80.0
WarmMat-070-2	70	6.50	20*42.7	0.5*13.0	840	3.5	68.6
WarmMat-080-2	80	7.43	20*48.8	0.5*14.9	960	4.0	60.0
WarmMat-090-2	90	8.36	20*54.9	0.5*16.7	1080	4.5	53.3
WarmMat-100-2	100	9.29	20*61.0	0.5*18.6	1200	5.0	48.0
WarmMat-110-2	110	10.22	20*67.1	0.5*20.4	1320	5.5	43.6
WarmMat-120-2	120	11.15	20*73.2	0.5*22.3	1440	6.0	40.0
WarmMat-145-2	145	13.47	20*88.4	0.5*26.9	1740	7.3	33.1
WarmMat-160-2	160	14.86	20*97.5	0.5*29.7	1920	8.0	30.0